

## PRIMABAKE CLASSIC

### Specification sheet V7

**Primabake Classic** is a **baking paper** made from virgin pulp with both surface sized with silicone.  
**A release paper with excellent heat stability, and is additionally hygienic and greaseproof.**

#### Typical end-use

An environmentally friendly baking paper ideal for a wide variety of uses from industrial applications through to domestic households.

INCREASING  
NUMBER OF BAKES

*Varies upon baked goods, time, temperature and operators.*



LIGHT

CLASSIC

STAR

#### Regulation and food contact approval

Meets regulatory international requirements on the food contact.

Statement compliance available for download on the page CERTIFICATION / Download certificates / Declaration of compliance

FSC® & PEFC® on request.

Specifications						
Property	Test Method	Unit	Typical value			
Grammage	ISO 536	g/m <sup>2</sup>	39		41	
Shade			White	Unbleached*	White	Unbleached*
Moisture	ISO 287	%	4.0	4.0	4.0	4.0
Thickness	ISO534	µm	48	48	50	50
ISO Brightness	ISO 2470-1	%	>76%	/	>76%	/
Bursting Strength after heating (200°C /20 mn)	ISO 2758	kPa	≥95	≥95	≥105	≥105
Water Absorbency Cobb 60	ISO 535	g/m <sup>2</sup>	14	14	14	14
Oil Absorbency Cobb 60	SCAN -P 37-77	g/m <sup>2</sup>	2,2	2,2	2,2	2,2
Sponge cake 8 mn/225 °C	PDL method	g/m <sup>2</sup>	≤32	≤32	≤32	≤32
Pretzel 25 mn/215 °C	PDL method		Not OK	Not OK	Not OK	Not OK

Paper tolerances	
Grammage: ± 1,5 g/m <sup>2</sup>	Water Absorbency Cobb 60: + 2,0 g/m <sup>2</sup>
Thickness: -2 / +3 µm	Oil Absorbency Cobb 60: + 2,8 g/m <sup>2</sup>

Available in reel and sheet			
Reel		Sheet	
Min. reel diameter	On demand	Box	500 or 1000
Max. reel diameter	115 cm	Packet	500
Cores	70/76/120/152 mm		

Finished goods tolerances	
Width customer tolerance: ( - 2mm,+ 0)	Size: ( - 2mm, +0)
Mill splice: Maxi 1 per reel with at least 60% of the reels without	
Outer diameter: ( -3, + 1 cm). Length ( 0/+200 m)	

\* Unbleached shade validated with the customer

Measurements made according to the standards and norms in place at time of publication.  
 Please contact your sales representative for more details.

Date: 1st December 2022

Validated: Hervé BRUNET-JAILLY